EcoTank Pro L6580



Fast business 4-in-1 colour ink tank printer with ultra-low-costper-page and an ultra-low total of ownership (TCO).

Print, scan, copy and fax with this easy-to-use EcoTank Pro Wi-Fi printer, that delivers an exceptionally low cost-per-page & reduces your energy consumption thanks

to Heat-Free PrecisionCore technology. A4 jobs can be accomplished quickly thanks to fast print & scan speeds, whilst two A4 250-sheet front trays, a 50-sheet rear feed, & a 50-sheet A4 ADF, ensures there is a high capacity of paper.

Keep on saving

Save every time you print with this EcoTank Pro. It features large ink tanks that you fill with low-cost ink bottles, delivering incredibly low costs-per-page. Thanks to Heat-Free PrecisionCore technology, you can also keep your energy consumption down to a minimum, saving on energy bills.

Time-saving features

Our fastest A4 device in its class, the L6580 offers a first page out time of just 5.5 seconds¹ and print speeds up to 25 pages per minute. The automatic document feeder can scan up to 27.5 images per minute.

Low user intervention

Minimising refills, this EcoTank Pro can print thousands of pages before needing more ink, while the two paper trays offer a capacity of 500-sheets. Free yourself from manual page loading with a generous 50-sheet rear feed and A4 ADF.

Easy to use and reliable

Selecting features is easy with the LCD colour touchscreen. And refilling the large front ink tanks is simple with the resealable, intuitive and drip-free ink bottles.


Print from almost anywhere

It's easy to print from mobiles, tablets and laptops using the L6580. With Wi-Fi and Wi-Fi Direct, you can send documents to print from smart devices using the Epson iPrint² app.

Achieve professional results

Edge-to-edge printing³ and DURABrite ET pigment ink helps you to achieve outstanding print quality on special projects .

DATASHEET / BROCHURE



KEY FEATURES

- Ultra-low cost, 4-in-1 A4 printer Economical ink tank system
- Fast print and scan speeds Print up to 25 ppm and scan up to 27.5 ipm
- Easy to use front ink tank Enjoy hassle and mess-free refills with enhanced ink bottles
- Mobile printing and connectivity Wi-Fi, Wi-Fi Direct, Ethernet & free mobile printing apps²
- Designed for business 2 x 250-sheet front tray, 50-sheet rear feed, 50-sheet ADF, PCL & PS3



PRODUCT SPECIFICATIONS

TECHNOLOGY			
Printing Method	PrecisionCore™ Print Head		
Nozzle Configuration	800 Nozzles Black, 800 Nozzles per Color		
Minimum Droplet Size	3,8 pl		
Ink Technology	DURABrite™ ET		
Category	Office Desktop		
All-in-One Functions	Print, Scan, Copy, Fax		
PRINT			
First Page Out	Monochrome 5,5 Seconds, Colour 6 Seconds		
Printing Speed ISO/IEC 24734	25 pages/min Monochrome, 25 pages/min Colour		
Duplex Printing Speed ISO/IEC 24734	21 A4 Pages/min Monochrome, 21 A4 Pages/min Colour		
Maximum Printing Speed	32 pages/min Monochrome (plain paper 75 g/m²), 32 pages/min Colour (plain paper 75 g/m²)		
Printing Resolution	4.800 x 2.400 DPI		
Printing Volume	66.000 pages per month		
	The maximum number of printed pages per month based on the performance capabilities of		
	the printer, including ISO rated print speeds and paper handling capabilities.		
Recommended Duty Cycle	200 - 3.300 pages per month		
Colours	Black, Cyan, Yellow, Magenta		
For detailed information on pr	inting speeds please visit http://www.epson.eu/testing.		
SCAN			
Double-sided scanning	Yes		
Single-sided scan speed (A4 black)	27,5 ipm with ADF scan 10 sec. with flatbed scan		
Doubled-sided scan speed (A4 black)	11 ipm with ADF scan		
Single-sided scan speed (A4 colour)	9 ipm with ADF scan 10 sec. with flatbed scan		
Doubled-sided scan speed (A4 colour)	6 ipm with ADF scan		
Optical Resolution	2.400 DPI x 1.200 DPI (Horizontal x Vertical)		
Advanced document	Scan to Email, Scan to FTP, Scan to Network folders		
integration			
Output formats	BMP, JPEG, TIFF, multi-TIFF, PDF, PNG		
Scanner type	Contact image sensor (CIS)		
FAX Type of fax	Walk-up black and white and colour fax canability		
Type of fax	Walk-up black and white and colour fax capability		
Fax Transmission Speed Error correction mode	Up to 33.6kbps / Approx. 3 sec/page		
Error correction mode Fax speed dials (max)	CCITU/ITU Group3 fax with Error Correction Mode		
	100 names and numbers		
Page memory Fax Functions	Up to 180 pages (ITU-T No.1 chart) PC Fax, Fax to E-mail, Memory Reception, Auto Redial, Address Book, Broadcast Fax, Fax Preview, Polling Reception		
CONNECTIVITY			
Network Printing Protocols	IPP, LDP, Port 9100, WSD		
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SLP, WSD, LLTD, Ping		
Network Protocol	IPv4, IPv6		
	Hi-Speed USB - compatible with USB 2.0 specification, Ethernet interface (100 Base-TX / 10		
Interfaces	Base-T), Wireless LAN IEEE 802.11b/g/n, Wi-Fi Direct, USB host, Near Field Communication (NFC)		

EcoTank Pro L6580

WHAT'S IN THE BOX

- 1 full set of ink (Bk 127ml, CMY 70ml)
- Power cable
- Installation/safety manual
- Driver and utilities (CD)
- Warranty document
- Main unit
- Quick Start Guide



PRODUCT SPECIFICATIONS

PAPER / MEDIA HANDLING			
Paper Formats	A4 (21.0x29.7 cm), Legal, A5 (14.8x21.0 cm), A6 (10.5x14.8 cm), B6, B5, No. 10 (Envelope), DL		
	(Envelope), C6 (Envelope), C4 (Envelope), Letter, Letter Legal		
Automatic Document Feed	50 pages		
Compatible Paper Weight	64 g/m² - 255 g/m²		
Duplex	Yes (A4, plain paper) 125 Sheets		
Output Tray Capacity			
Paper Tray Capacity 250 Sheets Standard, 550 Sheets Maximum			
Rear paper path (special	Yes		
media)			
Number of paper trays	3		
GENERAL			
Energy Use	19 Watt (standalone copying, ISO/IEC 24712 pattern), 0,8 Watt (sleep mode), 10 Watt (Ready)		
	0,2 Watt (Power off), TEC 0,14 kWh/week		
Supply Voltage	AC 100 V - 240 V, 50 Hz - 60 Hz		
Product dimensions	425 x 500 x 350 mm (Width x Depth x Height)		
Product weight	17,8 kg		
Compatible Operating	Mac OS 10.10.x, Mac OS 10.6+, Mac OS 10.7.x, Mac OS 10.8.x, Mac OS 10.9.x, Mac OS X		
Systems	10.11.x, Mac OS X 10.12.x, Mac OS X 10.13.x, Windows 10 (32/64 bit), Windows 7 (32/64 bit),		
	Windows 8 (32/64 bit), Windows 8.1 (32/64 bit), Windows Server 2008 R2, Windows Server		
	2012 R2, Windows Server 2016, Windows Vista (32/64 bit), Windows XP Professional x64		
	Edition SP2 or later, Windows XP SP3 or later (32-bit), Windows Server 2003 R2, Windows		
	Server 2003 SP2 or later, XP Professional x64 Edition		
Mobile and Cloud printing	Epson Connect (iPrint, Email Print, Remote Print Driver, Scan-to-Cloud), Apple AirPrint		
services			
Power supply	220V, 240V		
ADDITIONAL FEATURES			
Features	Touchscreen, Direct print from USB		
Panel	Type: Color, Touchscreen, Diagonal: 10,9 cm		
Media Handling	ADF 2-sided copy (A4, plain paper), ADF 2-sided fax (A4, plain paper), ADF 2-sided scan (A4,		
	plain paper), Automatic duplex (A4, plain paper)		
OTHER FEATURES			
Emulations	PCL3, PCL5c, PostScript 3		
OTHER			
Warranty	12 months Carry in, 200.000 pages		
	Optional warranty extension available		

SUPPLIES

 112 EcoTank Pigment Black ink bottle 	C13T06C14A	7.500 pages
 112 EcoTank Pigment Cyan ink bottle 	C13T06C24A	6.000 pages
 112 EcoTank Pigment Magenta ink bottle 	C13T06C34A	6.000 pages
 112 EcoTank Pigment Yellow ink bottle 	C13T06C44A	6.000 pages
 WF-78xx / ET-58xx / ET-166xx / L65xx / L151xx Maintenance Box 	C12C934591	

LOGISTICS INFORMATION

ѕки	C11CJ28403SA
EAN code	8715946677408
Country of Origin	Indonesia

EXCEPTION OF THE PROVIDENCE OF

EcoTank Pro L6580

INK YIELD DATA



* Approx. page yield based on ISO/IEC 24711/24712 or ISO/ IEC 29102/29103. Actual yield will vary depending on images printed and usage conditions. For more information visit http://www.epson.eu/pageyield

1. Determined in accordance with ISO/IEC 24734 showing the average of ESAT from the Office Category Test for default simplex. For more information visit www.epson.eu/testing 2. Requires a wireless connection to the internet. For

2. Requires a wireless connection to the internet. For more information, supported languages and devices please visit www.epsonconnect.com

3. The edge-to-edge print function is designed for occasional use. There is a limit to the number of prints that can be produced on this mode, before requiring replacement of the ink pad. After this limit is reached, printing on standard mode is still possible. Please refer to the user manual and warranty conditions for additional details.

