

AC1200 Whole Home Mesh Wi-Fi AP

MODEL: HC220-G5



Overview

HC220-G5 is a TP-Link Wi-Fi 5 Mesh AP based on the 802.11ac standard. Take your Wi-Fi to the next level while being backwards compatible with 802.11a/b/g/n/ac Wi-Fi standards.



AC1200 Dual **Band Wi-Fi**

Deliver total Wi-Fi speeds up to 1.2 Gbps (867 Mbps on 5 GHz, and 300 Mbps on 2.4 GHz) based on 802.11ac Wi-Fi technology.



Access

Take full advantage of the broadband with speed up to 1 Gbps through a gigabit WAN port and three gibabit Ethernet LAN ports for fast and reliable wired connections



Gigabit Internet Wireless, Hassle-free Installation

In TP-Link mesh Wi-Fi system, if a link is not usable for any reason, network resources could still be available via a second link as a fail-safe.



EasyMesh Feature Supported

HC220-G5 adopts EasyMesh technology, which has further improved and standardized Wi-Fi functions, such as Wi-Fi diagnostics, channel selection and traffic separation.



Specifications

Hardware

Interface

2× 10/100/1000 Mbps RJ45 LAN Ports 1× 10/100/1000 Mbps RJ45 WAN/LAN Port

Antenna

Internal antennas

• External Power Supply

12VDC/1.0A(For US)

• Dimensions (W * D * H)

3.9 x 3.9 x 3.5 in (100 x 100 x 89.5 mm)

• Button

WPS Button, Reset Button

• CPU

Dual-Core, 1.0 GHz

Wireless

• Wireless Standards

IEEE 802.11a/n/ac 5 GHz, IEEE 802.11b/g/n 2.4 GHz

Frequency

2.4 GHz and 5 GHz

• Signal Rate

867 Mbps at 5GHz, 300 Mbps at 2.4GHz

• Transmit Power

CE: <20 dBm (2.4 GHz), <23 dBm (5 GHz), FCC: <30 dBm

· Wireless Security

WPA/WPA2/WPA3 Personal, WPA/WPA2 Enterprise

• Wireless Function

Enable/Disable Wireless Radio, WMM, Wireless Statistics, Multi-SSID, Guest Network, TX Beamforming, MU-MIMO

Support EasyMesh

Seamless Roaming, Self-healing, Support 802.11k/v/r

Software

· Working Mode

Router Mode, AP Mode

• WAN Type

Dynamic IP/Static IP/PPPoE/PPTP/L2TP/Bridge Multi-EWAN

Protocols

Supports IPv4 and IPv6

Multi SSID

Up to 4 SSIDs for each band (including main SSID)

Features

Parental Control, Firewall, IPSEC VPN, IPv6, Port Forwarding, NAT Forwarding, Address Reservation, QoS(Quality of Service), CWMP, Network Diagnosis, Traffic Statistic, Cloud upgrade, 1024-QAM, MU-MIMO, OFDMA, EasyMesh

Management

Local management: WebGUI management, Aginet app management Remote management: TR-069, TR-181, TR369, TR-111, TR-143 Cloud management: TAUC

• DHCP

Server, Client

Firewall Security

DoS, SPI Firewall, IP and MAC Address Binding

- Support IPTV, IGMPV2/3 and IGMP Snooping
- Schedule

LED Schedule, Wi-Fi Schedule

Others

• System Requirements

Microsoft Windows 98SE, NT, 2000, XP, Vista™ or Windows 7, 8, 8.1,10, MAC OS, NetWare, UNIX or Linux Internet Explorer 11, Firefox 12.0, Chrome 20.0, Safari 4.0 browers or higher.

· Certification

CE. FCC. DFS

Environment

Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40°C~60°C (-40°F~140°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

• Package Contents

AC1200 Whole Home Mesh Wi-Fi AP 1× RJ45 Ethernet Cable

1× Power Adapter

1× Quick Installation Guide